

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 12/04/2024

Version: 1.3

**SECTION 1: IDENTIFICATION** 

**Product Identifier Product Form:** Mixture

Product Name: No Trans Fat Degreaser

Product Code: AFCO 2589 **Intended Use of the Product** 

Use of the Substance/Mixture: Heavy duty caustic foam cleaner for use on food processing equipment. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company **AFCO** 

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www.afcocare.com

**Emergency Telephone Number** 

Emergency Number : 1-800-424-9300 (CHEMTREC)

# **SECTION 2: HAZARDS IDENTIFICATION**

# **Classification of the Substance or Mixture**

# Classification (GHS-US)

Met. Corr. 1 H290 Acute Tox 5 (Oral) H303 H314 Skin Corr. 1A Eye Dam. 1 H318 Aquatic Acute 3 H402

**Label Elements GHS-US Labeling** 

**Hazard Pictograms (GHS-US)** 



Signal Word (GHS-US) : Danger

**Hazard Statements (GHS-US)** : H290 - May be corrosive to metals

H303- May be harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H402- Harmful to aquatic life

**Precautionary Statements (GHS-US)**: P234 - Keep only in original container.

P260 - Do not breathe vapors, mist, spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling. P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see section 4).

P363 - Wash contaminated clothing before reuse.

12/04/2024 EN (English US) 1/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container in accordance to local, regional, national, territorial, provincial, and international regulations.

#### **Other Hazards**

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contact with metals may evolve flammable hydrogen gas. **Unknown Acute Toxicity (GHS-US):** Not available.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**Substances:** Not available, product is a mixture.

#### Mixture:

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	40-50	Not classified
Sodium hydroxide	(CAS No) 1310-73-2	20-30	Met. Corr. 1, H290
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Ethanolamine	(CAS No) 141-43-5	10-20	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation: vapour), H332
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412
2-Butoxyethanol	(CAS No) 111-76-2	5-10	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation: vapour), H332
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
1,2-Propylene glycol	(CAS No) 57-55-6	1-5	Not classified
D-Glucopyranose, oligomeric, decyl octyl glycosides	(CAS No) 68515-73-1	1-5	Eye Dam. 1, H318

Exact percentage composition of substances and/or ingredients may be withheld as a trade secret, in accordance with [29 CFR § 1910.1200 App E].

Full text of H-phrases: see section 16.

# **SECTION 4: FIRST AID MEASURES**

# **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Get immediate medical advice/attention. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

12/04/2024 EN (English US) 2/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** Causes serious eye damage. Corrosive to eyes and skin.

**Inhalation:** May cause slight irritation to respiratory tract.

**Skin Contact:** Causes severe skin burns. **Eye Contact:** Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing

quickly to chemical burns.

Chronic Symptoms: Not available.

## Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

# **SECTION 5: FIRE-FIGHTING MEASURES**

# **Extinguishing Media**

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

## **Special Hazards Arising From the Substance or Mixture**

Fire Hazard: Not flammable.

**Explosion Hazard:** Product is not explosive.

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Toxic gas.

Corrosive to soft metals. May generate flammable hydrogen gas when in contact with soft metals.

#### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO<sub>2</sub>). Toxic fumes are released. Sodium oxides, nitrogen oxides.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

**Reference to Other Sections** 

Refer to section 9 for flammability properties.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

# **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Do not allow product to spread into the environment. Do NOT breathe (vapors, mist, spray). Do not get in eyes, on skin, or on clothing.

# **For Non-Emergency Personnel**

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

**For Emergency Personnel** 

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

#### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

## Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Contact competent authorities after a spill.

#### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

# **SECTION 7: HANDLING AND STORAGE**

# **Precautions for Safe Handling**

**Additional Hazards When Processed:** When heated to decomposition, emits toxic fumes. Corrosive vapors are released. Contact with soft metals may evolve flammable hydrogen gas.

12/04/2024 EN (English US) 3/10

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

# **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high temperatures, incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers. Soft metals.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s)

Heavy duty caustic foam cleaner for use on food processing equipment. For professional use only.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

OEL TWA (ppm)

OEL STEL (ppm)

OEL STEL (mg/m³)

ACGIH TWA (ppm)

OSHA PEL (TWA) (mg/m3)

NIOSH REL (TWA) (mg/m3)

OSHA PEL (TWA) (ppm)

#### **Control Parameters**

Mexico

Mexico

Mexico

**USA ACGIH** 

**USA OSHA** 

**USA OSHA** 

**USA NIOSH** 

Sodium hydroxide (1310-73-2)			
Mexico	OEL Ceiling (mg/m³)	2 mg/m³	
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³	
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³	
USA IDLH	US IDLH (mg/m³)	10 mg/m <sup>3</sup>	
Ontario	OEL Ceiling (mg/m³)	2 mg/m³	
Québec	PLAFOND (mg/m³)	2 mg/m <sup>3</sup>	
Ethanolamine (141-43-5)	Ethanolamine (141-43-5)		
Mexico	OEL TWA (mg/m³)	8 mg/m³	
Mexico	OEL TWA (ppm)	3 ppm	
Mexico	OEL STEL (mg/m³)	15 mg/m³	
Mexico	OEL STEL (ppm)	6 ppm	
USA ACGIH	ACGIH TWA (ppm)	3 ppm	
USA ACGIH	ACGIH STEL (ppm)	6 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	3 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	8 mg/m³	
USA NIOSH	NIOSH REL (TWA) (ppm)	3 ppm	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	15 mg/m³	
USA NIOSH	NIOSH REL (STEL) (ppm)	6 ppm	
USA IDLH	US IDLH (ppm)	30 ppm	
Ontario	OEL STEL (ppm)	6 ppm	
Ontario	OEL TWA (ppm)	3 ppm	
Québec	VECD (mg/m³)	15 mg/m³	
Québec	VECD (ppm)	6 ppm	
Québec	VEMP (mg/m³)	7.5 mg/m <sup>3</sup>	
Québec	VEMP (ppm)	3 ppm	
2-Butoxyethanol (111-76-2)			
Mexico	OEL TWA (mg/m³)	120 mg/m³	
•		1	

12/04/2024 EN (English US) 4/10

26 ppm

75 ppm

20 ppm

50 ppm

24 mg/m<sup>3</sup>

360 mg/m<sup>3</sup>

240 mg/m<sup>3</sup>

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Ontario	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m³)	97 mg/m³
Québec	VEMP (ppm)	20 ppm
1,2-Propylene glycol (57-55-6)		
Ontario	OEL TWA (mg/m³)	155 mg/m³
Ontario	OEL TWA (ppm)	50 ppm

#### **Exposure Controls**

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Alarm detectors should be used when toxic gases may be released. If user operations generate fumes, vapors, gas, or spray use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective goggles. Protective clothing. Gloves. Face shield.









Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosionproof clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A respirator is not needed under normal and intended conditions of product use. Whenever worker

exposure may exceed established regulatory exposure limits, use a NIOSH-approved respirator.

Other Information: When using, do not eat, drink or smoke.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<u>Information on Basic Physical and Chemical Properties</u>
--

Physical State : Liquid

**Appearance** : Clear, dark brown

Odor : Slight.

Odor Threshold : Not available

pH : >13

Relative Evaporation Rate (butylacetate=1): Not availableMelting Point: Not availableFreezing Point: Not availableBoiling Point: 107.2°C (224.96°F)

Flash Point : None
Auto-ignition Temperature : None

Decomposition Temperature: Not availableFlammability (solid, gas): Not availableLower Flammable Limit: Not availableUpper Flammable Limit: Not availableVapor Pressure: Not availableRelative Vapor Density at 20°C: Not available

Specific Gravity: 1.24Solubility: Complete.Partition coefficient: n-octanol/water: Not availableViscosity: Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact.

12/04/2024 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Explosion Data – Sensitivity to Static Discharge** : Not expected to present an explosion hazard due to static discharge.

#### **SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:** Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to soft metals.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Extremely high temperatures. Prolonged contact with soft metals. Incompatible materials.

**Incompatible Materials:** Strong acids and strong oxidizers. Soft metals.

Hazardous Decomposition Products: Carbon oxides (CO, CO<sub>2</sub>). Thermal decomposition generates: Toxic gases. Sodium oxides,

nitrogen oxides.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

# Information on Toxicological Effects - Product

Acute Toxicity: Not classified. LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns. pH: >13

Serious Eye Damage/Irritation: Causes serious eye damage. pH:>13

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

**Teratogenicity:** Not available. **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

**Symptoms/Injuries After Inhalation:** May cause slight irritation to respiratory tract.

Symptoms/Injuries After Skin Contact: Causes severe skin burns.
Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe

irritation progressing quickly to chemical burns.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)		
LD50 Oral Rat	>90000 mg/kg	
Ethanolamine (141-43-5)		
LD50 Oral Rat	1720 mg/kg	
LD50 Dermal Rabbit	1 ml/kg	
2-Butoxyethanol (111-76-2)		
LD50 Oral Rat	470 mg/kg	
LD50 Dermal Rat	1680 mg/kg	
LC50 Inhalation Rat (ppm)	450 ppm/4h	
ATE (oral)	470.000 mg/kg body weight	
ATE (dermal)	0.680 mg/kg body weight	
ATE (gases)	450.000 ppmV/4h	
ATE (vapors)	11.000 mg/l/4h	
IARC Group	3	
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.	
1,2-Propylene glycol (57-55-6)		
LD50 Oral Rat	20000 mg/kg	
LD50 Dermal Rabbit	20800 mg/kg	

12/04/2024 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 12: ECOLOGICAL INFORMATION**

#### **Toxicity**

Ecology - General: Harmful to aquatic life with long lasting effects.

Sodium hydroxide (1310-73-2)	
LC50 Fish 1	40 mg/l
Ethanolamine (141-43-5)	
LC50 Fish 1	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	65 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	15 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC50 Fish 2	3684 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
2-Butoxyethanol (111-76-2)	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
1,2-Propylene glycol (57-55-6)	
LC50 Fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	19000 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 Fish 2	41 (41 - 47) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

# **Persistence and Degradability**

No Trans Fat Degreaser (AFCO 2589)	
Persistence and Degradability	May cause long-term adverse effects in the environment.

#### **Bioaccumulative Potential**

lo Trans Fat Degreaser (AFCO 2589)		
Bioaccumulative Potential	Not established.	
2-Butoxyethanol (111-76-2)		
Log Pow	0.81 (at 25°C)	
Ethanolamine (141-43-5)		
Log Pow	-1.91 (at 25°C)	
1,2-Propylene glycol (57-55-6)		

# Mobility in Soil Not available.

#### **Other Adverse Effects**

BCF fish 1

Other Information: Avoid release to the environment.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Ecology – Waste Materials:** This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

# **SECTION 14: TRANSPORT INFORMATION**

# 14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

<1

Hazard Class: 8Identification Number: UN3266Label Codes: 8

Packing Group : III ERG Number : 154

14.2 In Accordance with IMDG

12/04/2024 EN (English US) 7/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Hazard Class : 8
Identification Number : UN3266
Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Packing Group : III
Identification Number : UN3266
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Packing Group: IIIHazard Class: 8Identification Number: UN3266

Label Codes : 8

# 8

# **SECTION 15: REGULATORY INFORMATION**

# **US Federal Regulations**

No Trans Fat Degreaser (AFCO 2589)		
Immediate (acute) health hazard.		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Sodium hydroxide (1310-73-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Ethanolamine (141-43-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
2-Butoxyethanol (111-76-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
1,2-Propylene glycol (57-55-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		

# EPA TSCA Regulatory Flag

EPA ISCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is
	made only from reactants included in a specified list of low concern
	reactants that comprises one of the eligibility criteria for the
	exemption rule.

#### D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

# **US State Regulations**

## Sodium hydroxide (1310-73-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances

12/04/2024 EN (English US) 8/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

#### Ethanolamine (141-43-5)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

# 2-Butoxyethanol (111-76-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

## **1,2-Propylene glycol (57-55-6)**

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

# D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

## **Canadian Regulations**

#### Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Ethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# 2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### 1,2-Propylene glycol (57-55-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision date** : 12/04/2024

Other Information : This document has been prepared in accordance with the SDS requirements of the

OSHA Hazard Communication Standard 29 CFR 1910.1200.

# **GHS Full Text Phrases:**

Acute Tox. 4 (Dermal)	Acute toxicity (Dermal) Category 4
Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4

12/04/2024 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Acute Tox. 5 (Oral)	Acute toxicity (oral) Category 5
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H303	May be harmful if swallowed.
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated

temperatures and pressures or may react with water with

some release of energy, but not violently.

**HMIS III Rating** 

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical

treatment is given.


Flammability : 0 - Minimal Hazard.
Physical : 1 - Slight Hazard.

# Party Responsible for the Preparation of This Document

AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329



North America SDS GHS 2015 (U.S., Can., Mex.)

12/04/2024 EN (English US) 10/10