

Solo-Gel Oven Cleaner (AFCO 2601) Safety Data Shoot

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 01/28/2025

Version: 1.4

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture

Product Name: Solo-Gel Oven Cleaner

Product Code: AFCO 2601 **Intended Use of the Product**

Use of the Substance/Mixture: Thickened caustic cleaner for use on food processing equipment. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company **AFCO**

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290 Skin Corr. 1A H314 Eve Dam. 1 H318

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary Statements (GHS-US): P234 - Keep only in original container.

P260 - Do not breathe vapors, mist, spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling. P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see section 4).

P363 - Wash contaminated clothing before reuse. P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container according to local, regional, national, territorial,

01/28/2025 EN (English US) 1/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contact with soft metals may evolve flammable hydrogen gas. Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	80-90	Not classified
Sodium hydroxide	(CAS No) 1310-73-2	5-10	Met. Corr. 1, H290
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
D-Glucopyranose, oligomeric, decyl octyl glycosides	(CAS No) 68515-73-1	1- 5	Eye Dam. 1, H318
b-Alanine, N-(2-carboxyethyl)-N-(3-	(CAS No) 64972-19-6	1-5	Not classified
(decyloxy)Propyl)-,monosodium salt			
Ethanolamine	(CAS No) 141-43-5	1-5	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation: vapour), H332
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412
Decyl phenoxybenzenedisulfonic acid,	(CAS No) 36445-71-3	0.1-1	Skin Irrit. 2, H315
disodium salt			Eye Dam. 1, H318
Cellulose, 2-hydroxyethyl ether	(CAS No) 9004-62-0	0.1 –1	Comb. Dust
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
			STOT SE 3, H335

Exact percentage composition of substances and/or ingredients may be withheld as a trade secret, in accordance with [29 CFR § 1910.1200 App E].

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Get immediate medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. Corrosive to eyes, respiratory system and skin.

Inhalation: None under normal and intended conditions of use.

Skin Contact: Causes severe skin burns and eye damage.

01/28/2025 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing

quickly to chemical burns.

Chronic Symptoms: Not available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to

soft metals. Explosive hydrogen gas when in contact with soft metals.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Toxic fumes are released. Sodium oxides, sulfur oxides, nitrogen oxides.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow product to spread into the environment. Do NOT breathe (vapors, mist, spray). Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes. Corrosive vapors are released. Contact with soft metals may evolve flammable hydrogen gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

01/28/2025 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high or low temperatures, incompatible materials.

Incompatible Materials: Acids. Strong oxidizers.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s): Thickened caustic cleaner for use on food processing equipment. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m³)	2 mg/m³
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³
USA IDLH	US IDLH (mg/m³)	10 mg/m ³
Ontario	OEL Ceiling (mg/m³)	2 mg/m³
Québec	PLAFOND (mg/m³)	2 mg/m³
Ethanolamine (141-43-5)		
Mexico	OEL TWA (mg/m³)	8 mg/m³
Mexico	OEL TWA (ppm)	3 ppm
Mexico	OEL STEL (mg/m³)	15 mg/m³
Mexico	OEL STEL (ppm)	6 ppm
USA ACGIH	ACGIH TWA (ppm)	3 ppm
USA ACGIH	ACGIH STEL (ppm)	6 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	3 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	8 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	3 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	15 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	6 ppm
USA IDLH	US IDLH (ppm)	30 ppm
Ontario	OEL STEL (ppm)	6 ppm
Ontario	OEL TWA (ppm)	3 ppm
Québec	VECD (mg/m³)	15 mg/m³
Québec	VECD (ppm)	6 ppm
Québec	VEMP (mg/m³)	7.5 mg/m ³
Québec	VEMP (ppm)	3 ppm

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. If user operations generate fumes, vapor, spray, or mist use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Protective goggles. Protective clothing. Gloves. Face shield.









Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosionproof clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: None needed under normal and intended conditions of use.

Other Information: When using, do not eat, drink or smoke.

01/28/2025 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Viscous liquid Clear, amber **Appearance**

Odor Slight.

Odor Threshold Not available

рΗ >13

Not available Relative Evaporation Rate (butylacetate=1) **Melting Point** Not available **Freezing Point** Not available **Boiling Point** 107.2°C (224.96°F)

Flash Point None **Auto-ignition Temperature** None

Decomposition Temperature Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available Upper Flammable Limit Not available **Vapor Pressure** Not available Relative Vapor Density at 20°C Not available

Specific Gravity 1.09 Solubility Complete. Partition coefficient: n-octanol/water Not available Viscosity Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact. Explosion Data - Sensitivity to Static Discharge Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to soft metals. Explosive hydrogen gas when in contact with soft metals.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Extremely high or low temperatures. Prolonged contact with soft metals. Incompatible materials.

Incompatible Materials: Acids, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Thermal decomposition generates: Sodium oxides, sulfor oxides, nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified. LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. (pH: >13)

Serious Eye Damage/Irritation: Causes serious eye damage. (pH: >13)

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available. Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: None under normal and intended conditions of use.

01/28/2025 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: Causes severe skin burns and eye damage.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)		
LD50 Oral Rat	>90000 mg/kg	
b-Alanine, N-(2-carboxyethyl)-N-(3-(decyloxy)Propyl)-,monosodium salt (64972-19-6)		
LD50 Oral Rat	16800 mg/kg	
Ethanolamine (141-43-5)		
LD50 Oral Rat	1720 mg/kg	
LD50 Dermal Rabbit	1 ml/kg	
Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)		
LD50 Oral Rat	>2000 mg/kg	
LD50 Dermal Rabbit	>2000 mg/kg	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

Ecology - General. Harriful to aquatic life with long lasting effects.		
Sodium hydroxide (1310-73-2)		
LC50 Fish 1	40 mg/l	
b-Alanine, N-(2-carboxyethyl)-N-(3-(decyloxy)Propyl)-,monosodium salt (64972-19-6)		
LC50 Fish 1	60.6mg/l (Exposure time: 96 h- Species: Pimephales promelas)	
LC50 Fish 2	100-250 mg/l (Exposure time: 24 h- Species: Pimephales promelas)	
Ethanolamine (141-43-5)		
LC50 Fish 1	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	65 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 Other Aquatic Organisms 1	15 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	
LC50 Fish 2	3684 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])	

Persistence and Degradability

Solo-Gel Oven Cleaner (AFCO 2601)	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Bioaccumulative Potential

Solo-Gel Oven Cleaner (AFCO 2601)	
Bioaccumulative Potential	Not established.
Ethanolamine (141-43-5)	
Log Pow	-1.91 (at 25°C)

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Hazard Class : 8
Identification Number : UN3266

01/28/2025 EN (English US) 8 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Label Codes: 8Packing Group: IIIERG Number: 154

14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Hazard Class : 8
Identification Number : UN3266

Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Packing Group : III

Identification Number : UN3266

Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L
14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

Packing Group : III Hazard Class : 8

Identification Number : UN3266

Label Codes : 8



^{*}Note: AF2601X (12 x1 QT) is allowed to ship as Limited Quantity.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Solo-Gel Oven Cleaner (AFCO 2601)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

b-Alanine, N-(2-carboxyethyl)-N-(3-(decyloxy)Propyl)-,monosodium salt (64972-19-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Ethanolamine (141-43-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Cellulose, 2-hydroxyethyl ether (9004-62-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

US State Regulations

Sodium hydroxide (1310-73-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)

01/28/2025 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New Jersey - Special Health Hazards Substances List

U.S. - New York - Occupational Exposure Limits - TWAs

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Ethanolamine (141-43-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New Jersey - Special Health Hazards Substances List

U.S. - New York - Occupational Exposure Limits - TWAs

U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour

U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

b-Alanine, N-(2-carboxyethyl)-N-(3-(decyloxy)Propyl)-,monosodium salt (64972-19-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Ethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Cellulose, 2-hydroxyethyl ether (9004-62-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION. INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 01/28/2025

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3

01/28/2025 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated

temperatures and pressures or may react with water with

some release of energy, but not violently.

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is

given.

Flammability : 0 - Minimal Hazard.

Physical : 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America SDS GHS 2015 (U.S., Can., Mex.)

01/28/2025 EN (English US) 9/9