

TECHNICAL DATA SHEET

800 Development Ave. ■ Chambersburg, PA 17201 ■ 1-800-345-1329 ■ www.afcocare.com



Snap (AFCO 3235)

GENERAL DESCRIPTION

Snap (AFCO 3235) is a low foaming, inhibited cleaner designed especially for use in high pressure spray washing equipment. It may also be used for soak applications and is safe for use on aluminum and other soft metals. Suggested use include cleaning beer kegs and bulk tanks, can washers, bakery pan washers, and milk-can washers.

PHYSICAL PROPERTIES

Appearance	:	Orange granular powder
Odor	:	Negligible
pH (1% solution)	:	11.9
Foam Level	:	Very low
Rinsing	:	Complete
Emulsification	:	Excellent

DIRECTIONS FOR USE

Recirculation Can Washers:

Use a solution containing ½ to 1 ounce of AFCO 3235 per gallon (4 to 8mL/L) of water at a temperature of 180°F (82°C).

Pan Washers:

Use a solution containing ¼ to ½ ounce of AFCO 3235 per gallon (2 to 4mL/L) of water.

Aluminum Barrels:

Use a solution containing 1 to 3 ounce(s) of AFCO 3235 per gallon (8 to 23mL/L) of water.

Tank Trucks:

Use a solution containing 4 to 8 ounces of AFCO 3235 per gallon (31.25 to 62.5mL/L) of water at a temperature of 180°F (82°C).

TECHNICAL DATA SHEET

800 Development Ave. ■ Chambersburg, PA 17201 ■ 1-800-345-1329 ■ www.afcocare.com



DANGER

Corrosive. Contact with undiluted product causes severe skin burns and serious eye damage. Handling of product without dilution may cause respiratory irritation in inadequate ventilation. Consult the product's Safety Data Sheet (SDS) for complete safety information.

NOTE

AFCO 3235 is U.S.D.A. acceptable for use in federally inspected meat, poultry and food processing plants.