



HyperFlex (AFCO 4365)

Safety Data Sheet

Revision Date: 09/09/2026

Version: 2.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Form: Mixture

Product Name: HyperFlex

Product Code: AFCO 4365

Intended Use of the Product

Use of the Substance/Mixture: Sanitizer for use on food processing equipment. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO
800 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)


SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Ox. Liq. 1	H271
Ox. Liq. 3	H272
Org. Perox. D	H242
Met. Corr. 1	H290
Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Inhalation: dust, mist)	H332
Skin Corr. 1A	H314
Eye Dam. 1	H318
STOT SE 3	H335
Aquatic Acute 2	H401

Label Elements

Hazard Pictograms



Signal Word

: Danger

Hazard Statements

: H242 - Heating may cause a fire
H271 - May cause fire or explosion; strong oxidizer
H272 - May intensify fire; oxidizer
H290 - May be corrosive to metals
H302+H332 - Harmful if swallowed or if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H401 - Toxic to aquatic life

Precautionary Statements

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
P220 - Keep/Store away from clothing, combustible materials, incompatible materials.
P221 - Take any precaution to avoid mixing with combustible materials, incompatible materials.
P234 - Keep only in original container.

HyperFlex (AFCO 4365)

Safety Data Sheet

P260 - Do not breathe vapors, mist, spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P283 - Wear fire/flammable resistant/retardant clothing.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P306+P360 - If on clothing: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a POISON CENTER or doctor/physician.
P312 - Call a POISON CENTER/doctor/physician if you feel unwell.
P321 - Specific treatment (see section 4).
P330 - If swallowed, rinse mouth.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use appropriate media for extinction.
P371+P380+P375 - In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
P390 - Absorb spillage to prevent material damage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P410 - Protect from sunlight.
P411+P235 - Store at temperatures not exceeding storage and handling temperatures. Keep cool.
P420 - Store away from other materials.
P501 - Dispose of contents/container in accordance to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contains an oxidizing material which may accelerate fire.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances: Not applicable, product is a mixture.

Mixture:

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	50-70	Not classified
Hydrogen peroxide	(CAS No) 7722-84-1	20 - 30	Ox. Liq. 1, H271 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation: vapour), H332 Skin Corr. 1A, H314 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

HyperFlex (AFCO 4365)

Safety Data Sheet

Acetic acid	(CAS No) 64-19-7	5 - 10	Flam. Liq. 3, H226 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Peroxyacetic acid	(CAS No) 79-21-0	5-10	Flam. Liq. 3, H226 Org. Perox. D, H242 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Aquatic Acute 1, H400
Nitric acid	(CAS No) 7697-37-2	5 – 10	Ox. Liq. 3, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318

The exact percentage (concentration) of the composition and/or ingredients has been withheld as a trade secret, in accordance with 29 CFR § [1910.1200\(i\)](#).

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Harmful if swallowed. Harmful if inhaled. Corrosive. Causes burns. Causes serious eye damage.

Inhalation: Harmful if inhaled. May cause respiratory irritation. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Eye Contact: Causes serious eye damage.

Ingestion: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: None.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable but, during fire product can decompose and generate oxygen which can initiate or promote combustion. Strong oxidizer.

Explosion Hazard: Heated containers may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Thermal decomposition generates: Corrosive vapors, acetic acid, and oxygen which supports combustion.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

HyperFlex (AFCO 4365)

Safety Data Sheet

Firefighting Instructions: Use water spray or fog for cooling exposed containers. For major fire and large quantities, evacuate area. Fight fire from protected location or maximum distance because of risk that heated containers could rupture.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Corrosive vapours, acetic acid, nitrogen oxides.

Other information: Do not allow run-off from fire fighting to enter drains or water courses. Chemical type extinguishers are not effective with peracetic acid or hydrogen peroxide.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do NOT breathe (vapors, mist, spray). Do not allow product to spread into the environment. Avoid all contact with skin, eyes, or clothing. Approach release from upwind.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Small spills may be flushed to an approved sewer line with generous amounts of water. For larger spills, dike well ahead of spill with non-reactive material such as sand. Cautiously neutralize spilled liquid. Spill may be neutralized with soda ash (sodium carbonate) broadcast on surface. Use 0.7 to 1 pound of soda ash for each gallon of spilled material. The resultant neutralized product will become carbon dioxide and water. Flush material with water and collect for disposal into plastic containers.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb spillage to prevent material damage. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to metals. Handle empty containers with care. May cause or intensify fire; oxidizer.

Handling Temperature: Not available.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: None known.

Storage Conditions: Store in a cool, dry, well-ventilated area. Do not store near reducing agents, fuels, organic materials, or other non-compatible materials. Do not store in direct sunlight, or near sources of ignition or heat. Product can be shipped on wooden pallets but should be stored on plastic pallets or plastic-covered pallets. Store drums in upright position only. Empty drums as thoroughly as possible. Triple rinse before disposal.

Incompatible Materials: Dirt, metals, strong bases, reducing agents, organic material, paper, wood, leather and heavy metals and their salts. May react violently with combustible materials. May react violently with finely divided metals. Never return product to original container.

Storage Temperature: Not available.

Storage Area: Store in a well-ventilated place. Keep cool. Protect from sunlight.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s)

Sanitizer for use on food processing equipment. For professional use only.

HyperFlex (AFCO 4365)

Safety Data Sheet

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Acetic acid (64-19-7)		
Mexico	OEL TWA (mg/m ³)	25 mg/m ³
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m ³)	37 mg/m ³
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	25 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	25 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	37 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Québec	VECD (mg/m ³)	37 mg/m ³
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m ³)	25 mg/m ³
Québec	VEMP (ppm)	10 ppm
Hydrogen peroxide (7722-84-1)		
Mexico	OEL TWA (mg/m ³)	1.5 mg/m ³
Mexico	OEL TWA (ppm)	1 ppm
Mexico	OEL STEL (mg/m ³)	3 mg/m ³
Mexico	OEL STEL (ppm)	2 ppm
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1.4 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1.4 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1 ppm
USA IDLH	US IDLH (ppm)	75 ppm
Ontario	OEL TWA (ppm)	1 ppm
Québec	VEMP (mg/m ³)	1.4 mg/m ³
Québec	VEMP (ppm)	1 ppm
Nitric acid (7697-37-2)		
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
Mexico	OEL TWA (ppm)	2 ppm
Mexico	OEL STEL (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (ppm)	4 ppm
USA ACGIH	ACGIH TWA (ppm)	2 ppm
USA ACGIH	ACGIH STEL (ppm)	4 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	2 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	2 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	4 ppm
USA IDLH	US IDLH (ppm)	25 ppm

HyperFlex (AFCO 4365)

Safety Data Sheet

Ontario	OEL STEL (ppm)	4 ppm
Ontario	OEL TWA (ppm)	2 ppm
Québec	VECD (mg/m ³)	10 mg/m ³
Québec	VECD (ppm)	4 ppm
Québec	VEMP (mg/m ³)	5.2 mg/m ³
Québec	VEMP (ppm)	2 ppm

Peroxyacetic acid (79-21-0)		
USA ACGIH	ACGIH STEL (ppm)	0.4 ppm

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. If user operations generate fumes, vapors, gas, or spray use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective clothing. Protective goggles. Gloves. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Thermal Hazard Protection: Wear suitable protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Particle Characteristics	: No data available.
Appearance	: Colorless
Odor	: Sharp, pungent, vinegar-like
Odor Threshold	: Not available
pH	: <1
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: >200°F (>93°C)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: 25 mm Hg (25°C/77°F)
Relative Vapor Density at 20°C (68°F)	: Not available
Specific Gravity	: 1.17
Solubility	: Complete
Log Pow	: Not available
Log Kow	: Not available

HyperFlex (AFCO 4365)

Safety Data Sheet

Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosive Properties	: Not expected to present an explosion hazard.
Oxidizing Properties	: May intensify fire; oxidizing liquid.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, generates acetic acid and oxygen which supports combustion.

Chemical Stability: Shelf life is one year from date of manufacture. Oxidizer - May intensify fire.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Open flames, elevated temperatures, any source of heat, direct sunlight. Combustibles such as paper, wood, and leather. Higher temperatures will accelerate decomposition resulting in a loss of assay.

Incompatible Materials: Dirt, metals, strong bases, reducing agents, organic material, paper, wood, leather and heavy metals and their salts. May react violently with combustible materials. May react violently with finely divided metals.

Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors, nitrogen oxides, acetic acid and oxygen which supports combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Harmful if swallowed. Harmful if inhaled.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not available.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified.

Potential Adverse Human Health Effects and Symptoms: Harmful if inhaled. Harmful if swallowed.

Symptoms/Injuries After Inhalation: Harmful if inhaled. May cause respiratory irritation. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: None.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Peroxyacetic acid (79-21-0)	
LD50 Oral Rat	263 mg/kg
LD50 Dermal Rabbit	1410 µl/kg
LC50 Inhalation Rat (mg/l)	0.3 mg/l (Exposure time: 1 h)
Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg
Acetic acid (64-19-7)	
LD50 Oral Rat	3310 mg/kg
LD50 Dermal Rabbit	1060 µl/kg
LC50 Inhalation Rat (mg/l)	11.4 mg/l/4h

HyperFlex (AFCO 4365)

Safety Data Sheet

ATE (oral)	3310.000 mg/kg body weight
ATE (dust, mist)	11.400 mg/l/4h
Hydrogen peroxide (7722-84-1)	
LD50 Oral Rat	376 mg/kg
LD50 Dermal Rabbit	2000 mg/kg
LC50 Inhalation Rat (mg/l)	2 g/m ³ (Exposure time: 4 h)
IARC Group	3
Nitric acid (7697-37-2)	
LC50 Inhalation Rat (mg/l)	0.13 mg/l (Exposure time: 4 h)
LC50 Inhalation Rat (ppm)	67 ppm/4h

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Toxic to aquatic life.

Acetic acid (64-19-7)	
LC50 Fish 1	79 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	65 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	75 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Hydrogen peroxide (7722-84-1)	
LC50 Fish 1	16.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	18 - 32 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	18 - 56 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Persistence and Degradability

HyperFlex (AFCO 4365)	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Bioaccumulative Potential

HyperFlex (AFCO 4365)	
Bioaccumulative Potential	Not established.

Peroxyacetic acid (79-21-0)	
BCF fish 1	(not bioaccumulative, rapid degradation)

Acetic acid (64-19-7)	
Log Pow	-0.31 (at 20°C)

Hydrogen peroxide (7722-84-1)	
BCF fish 1	(no bioaccumulation)

Nitric acid (7697-37-2)	
Log Pow	-2.3 (at 25°C)

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : OXIDIZING LIQUID, CORROSIVE, N.O.S. (Hydrogen peroxide, nitric acid, stabilized)
Hazard Class : 5.1
Identification Number : UN3098



HyperFlex (AFCO 4365)

Safety Data Sheet

Label Codes : 5.1, 8

Packing Group : II

ERG Number : 140

14.2 In Accordance with IMDG

Proper Shipping Name : OXIDIZING LIQUID, CORROSIVE, N.O.S. (Hydrogen peroxide, nitric acid, stabilized)

Hazard Class : 5.1

Identification Number : UN3098

Packing Group : II

Label Codes : 5.1, 8

EmS-No. (Fire) : F-H

EmS-No. (Spillage) : S-Q



14.3 In Accordance with IATA

Proper Shipping Name : OXIDIZING LIQUID, CORROSIVE, N.O.S. (Hydrogen peroxide, nitric acid, stabilized)

Packing Group : II

Identification Number : UN3098

Hazard Class : 5

Label Codes : 5.1, 8

ERG Code (IATA) : 5C



14.4 In Accordance with TDG

Proper Shipping Name : OXIDIZING LIQUID, CORROSIVE, N.O.S. (Hydrogen peroxide, nitric acid, stabilized)

Packing Group : II

Hazard Class : 5.1

Identification Number : UN3098

Label Codes : 5.1, 8



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

HyperFlex (AFCO 4365)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard. Reactive hazard. Fire hazard. Delayed (chronic) health hazard.
Peroxyacetic acid (79-21-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Listed on SARA Section 302 (Specific toxic chemical listings).	
Listed on SARA Section 313 (Specific toxic chemical listings).	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0%
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Acetic acid (64-19-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Hydrogen peroxide (7722-84-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Listed on SARA Section 302 (Specific toxic chemical listings).	
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 (concentration >52%)
Nitric acid (7697-37-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Listed on SARA Section 302 (Specific toxic chemical listings).	
Listed on SARA Section 313 (Specific toxic chemical listings).	

HyperFlex (AFCO 4365)

Safety Data Sheet

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
SARA Section 313 - Emission Reporting	1.0%

US State Regulations

Peroxyacetic acid (79-21-0)

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Acetic acid (64-19-7)

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Hydrogen peroxide (7722-84-1)

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Nitric acid (7697-37-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants With Proposed Risk Values
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations


HyperFlex (AFCO 4365)

Safety Data Sheet

Peroxyacetic acid (79-21-0)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Water (7732-18-5)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Acetic acid (64-19-7)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Hydrogen peroxide (7722-84-1)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Nitric acid (7697-37-2)
Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by those regulations.

SECTION 16: OTHER INFORMATION

Revision date	: 09/09/2026	
NFPA Health Hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.	
NFPA Fire Hazard	: 1 - Must be preheated before ignition can occur.	
NFPA Reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.	
NFPA Specific Hazard	: OX - This denotes an oxidizer, a chemical which can greatly increase the rate of combustion/fire.	
HMIS III Rating		
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given.	
Flammability	: 1 - Slight Hazard.	
Physical	: 1 - Slight Hazard.	

Preparation by:

AFCO
800 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Noth America SDS GHS Rev. 7 (U.S., Can., Mex.)