

# AFCO 4390 PERAFOAM



HMIS Ratings:  
Health: 1  
Flammability: 0  
Physical: 0

## WARNING

H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H402 - Harmful to aquatic life

---

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a POISON CENTER or doctor/physician.  
P321 - Specific treatment (see section 4).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

---

Contains: Water (CAS# 7732-18-5), Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C10-16-alkyl ethers, sodium salts (CAS# 68585-34-2), Sulfuric acid, mono-C10-16-alkyl esters, sodium salts (CAS# 68585-47-7), Pentasodium triphosphate (CAS# 7758-29-4), Lauryldimethylamine oxide (CAS# 1643-20-5)

**FOR USE WITH PER-OX:** As an adjunct to cleaning procedures this product may be added to PER-OX (AFCO 4325) and foamed on environmental or equipment surfaces using conventional foam-generating equipment. The resultant foam blend can be used on equipment, floors, walls, ceilings, drains, etc. and must be left on surface for a minimum of 1 minute or longer. On food contact surfaces do not exceed 6.1 oz. of Per-Ox per 6 gallons of water. **Directions for mixing:** Manually or mechanically blend 6 - 12 fl. oz. of this product (foam additive) and 1 - 6.1 fl. oz. of Per-Ox (4325) per 6 gallons of water. The dilution water must not exceed 150° F.

**GENERAL FOAM ADDITIVE USES:** Manually or mechanically blend 4-24 fl.oz. of this product to 6 gallons of water (0.6-4 fl. oz. per gal). and then add the 2nd product of your choice to the solution and mix thoroughly. Apply through a conventional foam generating device and adjust foam to desired characteristics.



AFCO  
550 Development Avenue  
Chambersburg, PA 17201  
www.afcocare.com

Tel. 800-345-1329  
Chemtrec Emergency No. 1-800-424-9300  
(Chemtrec Customer #CCN837)

US DOT: Not regulated

