



Liquid Pan Handler (AFCO 5253)

GENERAL DESCRIPTION

Liquid Pan Handler (AFCO 5253) is a low foaming inhibited alkaline liquid cleaner designed for use in high pressure spray washers used for cleaning bakery pans, cans, milk cans, and beer kegs. It can also be used for pipelines, bulk tanks, and soak applications. AFCO 5253 is safe to use on aluminum and other soft metals. Because it contains a defoamer, it will prevent the formation of excessive foam caused by certain soils during cleaning applications.

PHYSICAL PROPERTIES

Appearance	:	Clear, light amber liquid
Odor	:	Characteristic
pH (1% solution)	:	11.5
Specific Gravity	:	1.14 (9.50 lbs./gallon)
Foam	:	Very low

DIRECTIONS FOR USE

The directions listed below are general recommendations only. It is acceptable to use this product at higher or lower concentrations depending on soil load, chemical compatibility of surfaces to be cleaned and other operating conditions.

Pan Washers:

Use ¼ to 1½ ounce(s) of AFCO 5253 per gallon (6 to 11.7mL/L) of water at 110 to 170°F (43 to 76.6°C).

Can-Washers, Recirculating Lines:

Use 1 to 3 ounces of AFCO 5253 per gallon (8 to 23mL/L) of water at 110 to 170°F (43 to 76.6°C).

Aluminum Keg Washer:

Use 2 to 5 ounces of AFCO 5253 per gallon (16 to 39mL/L) of water at 110 to 170°F (43 to 76.6°C).

Tank Trucks:

Add 10 to 20 ounces of AFCO 5253 per gallon (78 to 156mL/L) of water at 110 to 170°F (43 to 76.6°C).

TECHNICAL DATA SHEET

800 Development Ave. ■ Chambersburg, PA 17201 ■ 1-800-345-1329 ■ www.afcocare.com



SAFETY

Safe to use on aluminum, brass, tin, galvanized, and stainless and mild steel when used as directed.

DANGER

Corrosive! Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.