



Liquid Smokehouse Cleaner (AFCO 5313)

GENERAL DESCRIPTION

Liquid Smokehouse Cleaner (AFCO 5313) is a low foaming, heavy duty caustic cleaner designed specifically for the circulation cleaning of smokehouses and ovens. It is a highly alkaline product with unique wetting and water conditioning agents.

AFCO 5313 can also be used in C.I.P. systems, H.T.S.T. pasteurizers and steam jacketed vessels. AFCO 5313 helps to control foam and minimize sudsing problems in circulation systems.

PHYSICAL PROPERTIES

Appearance	:	Clear, colorless to pale yellow liquid
Odor	:	Negligible
pH (1% solution)	:	12.9
Density	:	12.6 lbs./gallon
Foaming	:	Low

DIRECTIONS FOR USE

*The recommendations given below are general recommendations only.

AFCO 5313 can be used at any concentration necessary to clean the equipment. When used on food processing equipment, follow with portable water rinse.

Smokehouses, Ovens, & C.I.P. Systems:

Use ½ to 4 ounce(s) of AFCO 5313 per gallon (4 a 31mL/L) of water. (Strength varies due to types and amounts of soils encountered). Follow with a rinse of potable water.

Boil Outs:

Use 4 to 8 ounces of AFCO 5313 per gallon (31 a 62mL/L) of water. Follow with a rinse of potable water.

TECHNICAL DATA SHEET

800 Development Ave. ▪ Chambersburg, PA 17201 ▪ 1-800-345-1329 ▪ www.afcocare.com



Steam Generator & Other Pressure Systems:

Charge reservoir to yield ½ to ¾ ounce of AFCO 5313 per gallon (2 a 3.5mL/L) of water at the nozzle. Follow with a rinse of potable water.

SAFETY

Highly alkaline. Not for use on aluminum, galvanized, tin, or zinc.

DANGER

Corrosive! Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.