



Power Foam CL IN (AFCO 5315)

GENERAL DESCRIPTION

Power Foam CL IN (AFCO 5315) is a self-foaming chlorinated alkaline liquid detergent which is safe to use on aluminum and other soft metals without corrosive damage when used as directed. AFCO 5315 is specifically designed for foam and high-pressure spray cleaning of meat and poultry plants and is a complete product containing alkalis, water conditioners and chlorine, together with high foam wetting agents which make it effective even at cold water temperatures.

PHYSICAL PROPERTIES

Appearance	:	Clear, yellow-orange to amber liquid
pH (1% solution)	:	11.5 to 12.5
Specific Gravity	:	1.13 (9.4 lbs./gallon)
Foam Level	:	Very high and stable
Avail. Chlorine	:	1.7% (Min.)
Shelf Life	:	One year

DIRECTIONS FOR USE

This product is intended for Pressure Spray, Soak, and Manual Cleaning.

The common dilution factors listed below are general recommendations only. It is acceptable to use this product at higher or lower concentrations depending on soil load and other conditions. For use on soft metals, do not exceed 8 ounces of AFCO 5315 per gallon (62.5mL/L) of water at a temperature of 140°F/60°C. When used on food processing equipment, follow with a rinse of potable water.

Consult your AFCO/Zep representative for use directions.

Common Dilution Factors:

Ounces of AFCO 5315 per Gallon of Water	(mL/L)	AFCO 5315 Concentration (ppm)
3	23.4	23,440
4	31.2	31,250
5	39.0	39,060
6	46.8	46,875

TECHNICAL DATA SHEET

800 Development Ave. ▪ Chambersburg, PA 17201 ▪ 1-800-345-1329 ▪ www.afcocare.com



DANGER

Corrosive! Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.