

TECHNICAL DATA SHEET

800 Development Ave. ■ Chambersburg, PA 17201 ■ 1-800-345-1329 ■ www.afcocare.com



Power Foam HD (AFCO 5316)

GENERAL DESCRIPTION

Power Foam HD (AFCO 5316) is a highly alkaline heavy-duty liquid cleaner designed for pressure spray and foam cleaning of food processing equipment. It is an excellent choice for cleaning the heavy fatty soils encountered in poultry plant shackle cleaning, eviscerating areas, or soil encrusted smokehouses. It is also effective in removing greasy and burnt on soils found in the Baking Industry.

PHYSICAL PROPERTIES

Appearance	:	Clear, dark brown liquid
pH (1% Solution)	:	12.8
Density	:	10.5 lbs. per gallon
Foaming	:	Very high
Rinsing	:	Excellent

DIRECTIONS FOR USE

Pressure Spray:

Use ½ to 3 ounce(s) of AFCO 5316 per gallon (4 to 23ml/L) of hot water.

Foam Cleaning:

Use 3 to 8 ounces of AFCO 5316 per gallon (23 to 63ml/L) of hot water.

Tough, Burnt on Soils:

Before cleaning, rinse with hot (120-140°F/49-60°C), high-pressure water to remove as much particulate soil as possible.

Apply at a target concentration of 4 to 10 ounces of AFCO 5316 per gallon of hot (120-140°F/49-60°C) water. Allow a minimum contact time of 15 to 20 minutes. Using appropriate PPE - Hand scrub where needed. Follow with a rinse of hot (120-140°F/49-60°C), high pressure water.

Atomizing in Closed Spaces:

Use 6 to 10 ounces of AFCO 5316 per gallon (47 to 78ml/L) of water.

TECHNICAL DATA SHEET

800 Development Ave. ▪ Chambersburg, PA 17201 ▪ 1-800-345-1329 ▪ www.afcocare.com



SAFETY

Do not use on soft metals including tin, aluminum or galvanized steel!

DANGER

Corrosive! Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.

NOTES

AFCO 5316 is USDA accepted for use in federally inspected meat, poultry and food processing plants.