X-203
(AFCO 5370)

GENERAL DESCRIPTION

X-203 (AFCO 5370) is a concentrated alkaline cleaner designed for removal of dyes, petrolatum, and fragrances in immersion cleaning or CIP (Clean-In-Place) processes.

PHYSICAL PROPERTIES

Appearance	:	Clear, colorless liquid
Odor	:	None
pH (1% solution)	:	13 – 14
Specific Gravity	:	1.151
Viscosity (70°F/21°C)	:	4 centistokes

DIRECTIONS FOR USE

CIP and Spray Cleaner:

- *Light Duty* - Use 1 to 4 ounces of AFCO 5370 per gallon (8 to 31.2mL/L) of warm water. Spray, soak, or circulate for at least 10 minutes. Follow with a rinse of potable water.
- *Heavy Duty* - Use 6 to 10 ounces of AFCO 5370 per gallon (47 to 78.1mL/L) of water. Water temperature may be used up to 175°F, depending on soil conditions. Follow with a rinse of potable water.

Consult your *AFCO* technical representative for specific use applications.

SAFETY

Safe for use on stainless steel surfaces when used at the recommended dilution and contact time.

DANGER

Corrosive! Contact with undiluted product causes severe skin burns and serious eye damage. Consult the

product's Safety Data Sheet (SDS) for complete safety information.

To our knowledge, the information contained herein is accurate and reliable as of the date of preparation. AFCO makes no warranty, express or implied nor accepts any liability in connection with the information or its use. Recognizing that applicable laws may differ from one location to another and may change with time, the recipient is responsible for determining whether the information in this document is appropriate for recipient's use.