



Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 11/01/2024

Version: 1.2

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Gleam

Product Code: AFCO 5387

Intended Use of the Product

Use of the Substance/Mixture: Acid cleaner for soak, manual, and foam cleaning of food processing equipment. Effective for the removal of hardness scale and rust. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO
550 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329
www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290

Skin Corr. 1B H314

Eye Dam. 1 H318

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe mist, spray, vapors, fumes.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P321 - Specific treatment (see Section 4).
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards: May cause respiratory tract irritation. When heated to decomposition, emits toxic fumes. Contact with active metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	70-80	Not classified
Hydrogen chloride	(CAS No) 7647-01-0	5-10	Met. Corr. 1, H290 Acute Tox. 3 (Inhalation: gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Phosphoric acid	(CAS No) 7664-38-2	5-10	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
Sodium xylene sulfonate	(CAS No) 1300-72-7	1-5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	(CAS No) 85536-14-7	1-5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Decyl phenoxybenzenedisulfonic acid, disodium salt	(CAS No) 36445-71-3	1-5	Skin Irrit. 2, H315 Eye Dam. 1, H318
Nonylphenol ethoxylates	(CAS No) 9016-45-9	1-5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Chronic 2, H411
2-Butoxyethanol	(CAS No) 111-76-2	1-5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation: vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Exact percentage composition of substances and/or ingredients may be withheld as a trade secret, in accordance with [29 CFR § 1910.1200 App E].

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Inhalation: May cause respiratory tract irritation.

Skin Contact: Causes severe skin burns.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive, however contact with metals may release explosive hydrogen gas.

Reactivity: Thermal decomposition generates: Corrosive vapors and toxic fumes. Reacts violently with strong bases.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not breath fumes from fires or vapors from decomposition. Stop leak if safe to do so. Do not allow run-off from fire fighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sulfur oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Do not breathe mist or spray. Avoid contact with metal.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Eliminate ignition sources. Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Cautiously neutralize spill. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Ventilate area. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Store in original container. Store locked up. Keep container closed when not in use. Keep away from heat, extremely high temperatures and incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers.

Specific End Use(s)

For professional use only. Acid cleaner for soak, manual, and foam cleaning of food processing equipment. Effective for the removal of hardness scale and rust.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Phosphoric acid (7664-38-2)		
Mexico	OEL TWA (mg/m ³)	1 mg/m ³
Mexico	OEL STEL (mg/m ³)	3 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
USA ACGIH	ACGIH STEL (mg/m ³)	3 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1 mg/m ³
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	3 mg/m ³
USA IDLH	US IDLH (mg/m ³)	1000 mg/m ³
Ontario	OEL STEL (mg/m ³)	3 mg/m ³
Ontario	OEL TWA (mg/m ³)	1 mg/m ³
Québec	VECD (mg/m ³)	3 mg/m ³
Québec	VEMP (mg/m ³)	1 mg/m ³
Hydrogen chloride (7647-01-0)		
Mexico	OEL Ceiling (mg/m ³)	7 mg/m ³
Mexico	OEL Ceiling (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	2 ppm
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	7 mg/m ³
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	7 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Ontario	OEL Ceiling (ppm)	2 ppm
Québec	PLAFOND (mg/m ³)	7.5 mg/m ³
Québec	PLAFOND (ppm)	5 ppm
2-Butoxyethanol (111-76-2)		
Mexico	OEL TWA (mg/m ³)	120 mg/m ³
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m ³)	360 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	24 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Ontario	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m ³)	97 mg/m ³
Québec	VEMP (ppm)	20 ppm

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use with adequate ventilation. Use effective ventilation system to maintain air concentrations below occupational exposure limits. Ensure all national/local regulations are observed.

Personal Protective Equipment: Safety glasses. Face shield. Corrosionproof clothing. Gloves. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If workers are exposed to airborne concentrations above the exposure limits, they must use NIOSH certified respirators.

Consumer Exposure Controls: Do not eat, drink, or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, colorless to pale yellow
Odor	: Moderate acidic
Odor Threshold	: Not available
pH	: < 1
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 97.8°C (208.04°F)
Flash Point	: Not flammable
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not flammable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Specific Gravity	: 1.08
Solubility	: Complete in water.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors, toxic fumes. Reacts violently with strong bases.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Extremely high temperatures. Incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors. Carbon oxides (CO, CO₂). Hydrogen chloride. Sodium oxides. Sulfur oxides.

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns. **pH:** <1

Serious Eye Damage/Irritation: Causes serious eye damage. **pH:** <1

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: May cause respiratory tract irritation.

Symptoms/Injuries After Skin Contact: Causes severe skin burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)	
LD50 Oral Rat	>2000 mg/kg
LD50 Dermal Rabbit	>2000 mg/kg
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
LD50 Oral Rat	1219 mg/kg
Phosphoric acid (7664-38-2)	
LD50 Oral Rat	1530 mg/kg
LD50 Dermal Rabbit	2730 mg/kg
LC50 Inhalation Rat	>850 mg/m ³ (Exposure time: 1 h)
Hydrogen chloride (7647-01-0)	
LD50 Oral Rat	700 mg/kg
LD50 Dermal Rabbit	>5010 mg/kg
LC50 Inhalation Rat	781 ppm/4h (reported as 3124 ppm/1 h)
IARC Group	3
Sodium xylene sulfonate (1300-72-7)	
LD50 Oral Rat	1000 mg/kg
LD50 Dermal Rabbit	>2000 mg/kg
Nonylphenol ethoxylates (9016-45-9)	
LD50 Oral Rat	2590 mg/kg
LD50 Dermal Rabbit	1780 µl/kg
2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rat	1680 mg/kg
LC50 Inhalation Rat (ppm)	450 ppm/4h
ATE (dermal)	0.680 mg/kg body weight
ATE (gases)	450.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IARC Group	3
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Not classified.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
LC50 Fish 1	5.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [flow-through])
EC50 Daphnia 1	5.2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	1.67 mg/l (Exposure time: 96h - Species: Lepomis macrochirus)

2-Butoxyethanol (111-76-2)	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

Persistence and Degradability

Gleam (AFCO 5387)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Gleam (AFCO 5387)	
Bioaccumulative Potential	Not established.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
Log Pow	2 (at 23°C)

2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (at 25°C)

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations. RCRA Waste Code: D002 (Corrosive Material).

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)
Hazard Class : 8
Identification Number : UN3264
Label Codes : 8
Packing Group : II
Marine Pollutant : Yes
ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)
Hazard Class : 8
Identification Number : UN3264
Packing Group : II
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Marine pollutant : Yes
MFAG Number : 154



14.3 In Accordance with IATA

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)
Packing Group : II
Identification Number : UN3264
Hazard Class : 8
Label Codes : 8



ERG Code (IATA) : 8L

14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Phosphoric acid, hydrochloric acid)
Packing Group : II
Hazard Class : 8
Identification Number : UN3264
Label Codes : 8



Marine Pollutant (TDG) : Yes

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Gleam (AFCO 5387)		
SARA Section 311/312 Hazard Classes		Immediate (acute) health hazard.
SARA Section 313 - The following components are subject to reporting levels established by SARA Title III. Section 313		
Component	CAS Number	% in Product
2-Butoxyethanol	111-76-2	2.0
Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Phosphoric acid (7664-38-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Hydrogen chloride (7647-01-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Listed on SARA Section 302 (Specific toxic chemical listings).		
Listed on SARA Section 313 (Specific toxic chemical listings).		
SARA Section 302 Threshold Planning Quantity (TPQ)	500 (gas only)	
SARA Section 313 - Emission Reporting	1.0% (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)	
Water (7732-18-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Sodium xylene sulfonate (1300-72-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
Nonylphenol ethoxylates (9016-45-9)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		
2-Butoxyethanol (111-76-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory.		

US State Regulations

Phosphoric acid (7664-38-2)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Hydrogen chloride (7647-01-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - Ceilings
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Sodium xylene sulfonate (1300-72-7)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Nonylphenol ethoxylates (9016-45-9)

U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

2-Butoxyethanol (111-76-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - Skin Designations
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Decyl phenoxybenzenedisulfonic acid, disodium salt (36445-71-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Phosphoric acid (7664-38-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Hydrogen chloride (7647-01-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium xylene sulfonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Nonylphenol ethoxylates (9016-45-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 11/06/2024

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4
Acute Tox. 3 (Inhalation: gas)	Acute toxicity (inhalation: gas) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



Gleam (AFCO 5387)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is given.
Flammability	: 0 - Minimal Hazard.
Physical	: 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO
550 Development Ave.
Chambersburg, PA 17201
Tel. 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)