



Gleam (AFCO 5387)

GENERAL DESCRIPTION

Gleam (AFCO 5387) is a concentrated blend of inorganic and organic acids. It is high foaming and is designed for soak, manual, and foam cleaning. AFCO 5387 is used for the general cleaning of equipment and is especially effective for the removal of hardness scale and rust.

PHYSICAL PROPERTIES

Appearance	:	Clear, pale-yellow liquid
Odor	:	Moderate
pH (1% solution)	:	1.75
Density	:	9.0 lbs./gallon
Foaming	:	High
Rinsing	:	Complete

DIRECTIONS FOR USE

Manual & Soak Cleaning of Equipment:

For general cleaning and removal of hardness scale, use ½ to 2 ounce(s) of AFCO 5387 per gallon (4 to 16mL/L) of water. Rinse equipment well after application.

Rust Removal:

Add 10 to 15 ounces of AFCO 5387 per gallon (78 to 117mL/L) of warm water. Allow 15 to 30 minutes contact time before rinsing.

Foam Cleaning of Equipment:

For general cleaning and removal of hardness scale, use 4 to 6 ounces of AFCO 5387 per gallon (31 to 47mL/L) of water. Rinse equipment well after application.

TECHNICAL DATA SHEET

550 Development Ave. ■ Chambersburg, PA 17201 ■ 1-800-345-1329 ■ www.afcocare.com



SAFETY

Safe on stainless steel when used at recommended dilutions.

Do not use on stainless steel at temperatures above 130°F/54.4°C.

Do Not use on soft metals such as aluminum!

DANGER

Corrosive. Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.

NOTE

AFCO 5387 is U.S.D.A. acceptable for use in federally inspected meat, poultry and food processing plants.