



Power Foam IN (AFCO 5390)

GENERAL DESCRIPTION

Power Foam IN (AFCO 5390) is a self-foaming, alkaline, liquid cleaner designed for the foam cleaning of food processing equipment. It is also effective for spray and soak cleaning operations. AFCO 5390 has high water conditioning and fat emulsifying properties which leaves equipment bright and free of hard water and oily films.

AFCO 5390 is safe on all ferrous metals and galvanized surfaces when used as recommended. It is well suited for use with automatic feeding equipment which eliminates dissolving problems encountered with powdered products.

PHYSICAL PROPERTIES

Appearance	:	Clear, Pale-Yellow Liquid
Odor	:	Mild
pH (1% solution)	:	11.6
pH (concentrate)	:	12.5
Density	:	9.33 lbs./gallon
Specific Gravity	:	1.12
Rinsing	:	Excellent
Foam Ability	:	Excellent
Hard Water Tolerance	:	High

DIRECTIONS FOR USE

Foam Applications:

Add 2½ to 4 ounces of AFCO 5390 per gallon (19.5 to 31.7mL/L) of water.

Pressure Spray Applications:

Use at ½ to 1½ ounce(s) of AFCO 5390 per gallon (4 to 12mL/L) of warm water (110 to 130°F/43to 54°C).

TECHNICAL DATA SHEET

800 Development Ave. ▪ Chambersburg, PA 17201 ▪ 1-800-345-1329 ▪ www.afcocare.com



DANGER

Corrosive. Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.

NOTE

AFCO 5390 is U.S.D.A. acceptable for use in federally inspected meat, poultry and food processing plants.