



# Lubricon SW (AFCO 5523)

## GENERAL DESCRIPTION

Lubricon SW (AFCO 5523) is a water soluble, completely biodegradable conveyor lubricant which has been proven to be an effective yet economical lubricant for glass bottles and cans in both dairies and breweries. AFCO 5523 is a mixture of water, fatty acid soaps, chelating agents, and synthetic detergents.

AFCO 5523 is designed for use in soft to moderately hard water.

## PHYSICAL PROPERTIES

Appearance	:	Clear, amber liquid
Odor	:	Mild
pH (1% solution)	:	>13
Specific Gravity	:	1.01
Hardness Tolerance	:	(90:1 - 50 ppm as CaCO <sub>3</sub> /130:1 - 35 ppm as CaCO <sub>3</sub> )

## DIRECTIONS FOR USE

AFCO 5523 is recommended for use in soft to medium hard water. Typical dilution range is 90:1 to 130:1.

Never use a dilution that is cloudy or milky. This tends to block lines and leaves a residue on conveyors. Increase concentration until solution is clear.

Consult your *AFCO/Zep* technical representative for specific use applications.

## WARNING

Causes skin and eye irritation. Wash thoroughly after handling. In case of contact, immediately flush skin or eyes with plenty of water. For eye contact, get medical attention immediately. Consult the product's Safety Data Sheet (SDS) for complete safety information.