



Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 11/12/2024

Version: 1.1

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Desana IC

Product Code: AFCO 5542

Intended Use of the Product

Chlorinated CIP cleaner. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO

550 Development Avenue

Chambersburg, PA 17201

T: 800-345-1329

www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290

Acute Tox. 4 (Oral) H302

Skin Corr. 1B H314

Eye Dam. 1 H318

STOT SE 3 H335

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05



GHS07

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H290 - May be corrosive to metals
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe vapors, mist, spray.
P261 - Avoid breathing fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P312 - Call a POISON CENTER/doctor/physician if you feel unwell.
P321 - Specific treatment (see section 4).
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards: May be corrosive to the respiratory tract. When heated to decomposition, emits toxic fumes. Contact with metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

| Name of Hazardous Ingredients | Product identifier | % (w/w) | Classification (GHS-US) |
|-------------------------------|--------------------|----------|--|
| Potassium hydroxide | (CAS No) 7681-52-9 | 10 - 25 | Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 |
| Sodium hypochlorite | (CAS No) 1310-58-3 | 2.5 - 10 | Met. Corr. 1, H290 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Drench affected area with water for several minutes. Immediately call a POISON CENTER or doctor/physician.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Corrosive. Causes severe skin burns. Causes serious eye damage. May cause irritation of respiratory tract.

Inhalation: May cause respiratory irritation.

Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chronic Symptoms: Not available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Contact with soft metals may evolve flammable hydrogen gas.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Potassium oxides. Sodium oxides. Hydrogen chloride.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do NOT breathe (vapors, mist, spray). Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid. Absorb and/or contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill. Absorb spillage to prevent material damage.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes. May be corrosive to soft metals. Contact with soft metals may evolve flammable hydrogen gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a well-ventilated place. Keep container tightly closed. Keep/Store away from heat, direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids. Soft metals. Nitrogen containing compounds, ammonium compounds.

Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific End Use(s)

Cleaning material/ Detergent. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Potassium hydroxide (1310-58-3) | | |
|---------------------------------|--|-----------------------|
| Mexico | OEL Ceiling (mg/m ³) | 7 mg/m ³ |
| Mexico | OEL Ceiling (ppm) | 5 ppm |
| USA ACGIH | ACGIH Ceiling (ppm) | 2 ppm |
| USA OSHA | OSHA PEL (Ceiling) (mg/m ³) | 7 mg/m ³ |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 5 ppm |
| USA NIOSH | NIOSH REL (ceiling) (mg/m ³) | 7 mg/m ³ |
| USA NIOSH | NIOSH REL (ceiling) (ppm) | 5 ppm |
| USA IDLH | US IDLH (ppm) | 50 ppm |
| Ontario | OEL Ceiling (ppm) | 2 ppm |
| Québec | PLAFOND (mg/m ³) | 7.5 mg/m ³ |
| Québec | PLAFOND (ppm) | 5 ppm |

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. If user operations generate fumes, gas, vapors, spray, or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective clothing. Protective goggles. Gloves. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A respirator is not needed under normal and intended conditions of use. If airborne concentrations of vapor or mist are expected to exceed exposure limits, use NIOSH-approved respirator.

Thermal Hazard Protection: Wear suitable protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

| | |
|--|---------------------------------|
| Physical State | : Liquid |
| Appearance | : Violet |
| Odor | : Chlorine-like |
| Odor Threshold | : Not available |
| pH | : 12 |
| Relative Evaporation Rate (butylacetate=1) | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : 100°C (212°F) |
| Flash Point | : Not available |
| Auto-ignition Temperature | : Product is not self-igniting. |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |

Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|---|
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |
| Relative Vapor Density at 20°C (68°F) | : Not available |
| Specific Gravity | : 1.268 g/cm ³ |
| Solubility | : Complete in water. |
| Partition coefficient: n-octanol/water | : Not available |
| Viscosity | : Not available |
| Explosion Data – Sensitivity to Mechanical Impact | : Not expected to present an explosion hazard due to mechanical impact. |
| Explosion Data – Sensitivity to Static Discharge | : Not expected to present an explosion hazard due to static discharge. |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Contact with soft metals may evolve flammable hydrogen gas.

Chemical Stability: Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Strong acids. Soft metals. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Sodium oxides, potassium oxides. Thermal decomposition generates: Toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns. **pH:** 12

Serious Eye Damage/Irritation: Causes serious eye damage. **pH:** 12

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| Potassium hydroxide (1310-58-3) | |
|--|---------------------------|
| LD50 Oral Rat | 214 mg/kg |
| ATE (oral) | 333.000 mg/kg body weight |
| Sodium hypochlorite (7681-52-9) | |
| LD50 Oral Rat | 8200 mg/kg |
| LD50 Dermal Rabbit | >10000 mg/kg |
| IARC Group | 3 |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: Harmful to aquatic life.

| Sodium hypochlorite (7681-52-9) | |
|--|---|
| LC50 Fish 1 | 0.06 (0.06 - 0.11) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 0.033 - 0.044 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |

Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|----------------|--|
| LC50 Fish 2 | 4.5 (4.5 - 7.6) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 0.033 (0.033 - 0.044) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |

Persistence and Degradability

| | |
|-------------------------------|------------------|
| Desana IC (AFCO 5542) | |
| Persistence and Degradability | Not established. |

Bioaccumulative Potential

| | |
|------------------------------|------------------|
| Desana IC (AFCO 5542) | |
| Bioaccumulative Potential | Not established. |

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

RCRA Waste Code: D002 (Corrosive Material).

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)
Hazard Class : 8
Identification Number : UN3266
Label Codes : 8
Packing Group : III
Marine Pollutant : Yes
ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)
Hazard Class : 8
Identification Number : UN3266
Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Marine pollutant : Yes



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)
Packing Group : III
Identification Number : UN3266
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)
Packing Group : III
Hazard Class : 8
Identification Number : UN3266
Label Codes : 8



Desana IC (AFCO 5542)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| | |
|--|--|
| Desana IC (AFCO 5542) | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard. Delayed (chronic) health hazard. |
| Potassium hydroxide (1310-58-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory. | |
| Sodium hypochlorite (7681-52-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory. | |

US State Regulations

| |
|--|
| Potassium hydroxide (1310-58-3) U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New Jersey - Environmental Hazardous Substances List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS) U.S. - New York - Occupational Exposure Limits - Ceilings U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term |
| Sodium hypochlorite (7681-52-9) U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term |

Canadian Regulations

| |
|--|
| Potassium hydroxide (1310-58-3) |
| Listed on the Canadian DSL (Domestic Substances List) inventory. |
| Sodium hypochlorite (7681-52-9) |
| Listed on the Canadian DSL (Domestic Substances List) inventory. |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 11/12/2024
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|---------------------|--|
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Acute 3 | Hazardous to the aquatic environment - Acute Hazard Category 3 |

Desana IC (AFCO 5542)

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-------------------|--|
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Met. Corr. 1 | Corrosive to metals Category 1 |
| Skin Corr. 1A | Skin corrosion/irritation Category 1A |
| Skin Corr. 1B | Skin corrosion/irritation Category 1B |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H290 | May be corrosive to metals |
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |
| H335 | May cause respiratory irritation |
| H400 | Very toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur.

Flammability : 0 - Minimal Hazard.

Physical : 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO
550 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)