



Smart Track Basic (AFCO 5546)

GENERAL DESCRIPTION

Smart Track Basic (AFCO 5546) is a multi-purpose dry conveyor lubricant designed for use on plastic or stainless-steel conveyor belts. AFCO 5546 is designed to reduce or eliminate PET stress cracking precursors such as conveyor soils or lubricant make-up water alkalinity. By maintaining the conveyors in a cleaner condition, AFCO 5546 allows plant operators to run their conveyor lines at their designed speeds. AFCO 5546 will reduce the time and chemicals required for post-production conveyor cleaning. AFCO 5546 is usually applied dry (no water added) but can also be used water added in certain situations with superior performance to traditional lubes. When applied dry it significantly reduces water usage and BOD to the plant wastewater effluent. AFCO 5546 has zero alkalinity.

BENEFITS

Dry application methodology contributes to:

- Economy.
- Increased line efficiency.
- Package safety.
- Increased personnel safety.
- Reduced plant effluent.
- Reduced operating costs.
- Food grade – NSF registered (H1).

PHYSICAL PROPERTIES

Appearance	:	Milky-white liquid
pH (as is)	:	7.0
Density	:	8.33 lbs./gallon
Alkalinity	:	Zero

DIRECTIONS FOR USE

AFCO 5546 is suitable for use in all central plant lubrication systems. It may be used as a mobility enhancer and/or friction-reducing agent on most types of plastic surfaces.

TECHNICAL DATA SHEET

800 Development Ave. ▪ Chambersburg, PA 17201 ▪ 1-800-345-1329 ▪ www.afcocare.com



Consult your *AFCO/Zep* representative for specific guidelines and application recommendations.

CORROSIVE DATA

Safe for use on all metal surfaces.

SAFETY

AFCO 5546 is not expected to present a significant health hazard under anticipated conditions of normal use. Consult the product's Safety Data Sheet (SDS) for complete safety information.