

TECHNICAL DATA SHEET

800 Development Ave. • Chambersburg, PA 17201 • 1-800-345-1329 • www.afcocare.com



Clean Trac S (AFCO 5560)

GENERAL DESCRIPTION

Clean Trac S (AFCO 5560) is a completely synthetic, low BOD, concentrated conveyor lubricant. AFCO 5560 has excellent detergency and is not affected by hard water. The ingredients in AFCO 5560 keep soils from building up on conveyor lines, keeping conveyors clean and working with optimal efficiency.

PHYSICAL PROPERTIES

Appearance	:	Clear to slightly hazy amber liquid
pH (1% Solution)	:	10.6
Density	:	8.83 lbs./gallon

DIRECTIONS FOR USE

The suggested use levels for *AFCO 5560* range from 200-1 (0.5%) to 600-1 (0.17%). Dilution ratio does vary with conveyor loads and/or type of conveyor.

The most economical dilution rate will be determined by your *AFCO/Zep* Representative.

AFCO 5560 is cationic and is not compatible with most conveyor lubricants which are anionic. Flush lines and nozzles with 80 to 100°F (26.6 to 38°C) water for 20 minutes when changing over from an anionic.

CORROSION DATA SAFETY

Safe to use on stainless steel, galvanized steel, copper, brass, and aluminum when used at the recommended use dilution.

DANGER

Corrosive! Contact with the product undiluted causes severe burns to the skin and serious damage to the eyes. Consult the product's Safety Data Sheet (SDS) for complete safety information.