

TECHNICAL DATA SHEET

800 Development Ave. • Chambersburg, PA 17201 • 1-800-345-1329 • www.afcocare.com



Hydragenix® ProKleen (AFCO 5756)

GENERAL DESCRIPTION

Hydragenix® ProKleen (AFCO 5756) is a concentrated, environmentally preferable, non-butyl, heavy duty alkaline cleaner and degreaser effective at removing soils from stainless steel, floors, walls, hoods, ovens, grills, machinery, glass and many other hard surfaces. AFCO 5756 is specially formulated for removing fat, grease, and oily soils from food processing equipment in dairies, bakeries, meat, poultry, and other food and beverage processing facilities.

MAJOR BENEFITS

- ✓ Powerful Cleaning Action - Rapidly removes dirt, grease and grime from a wide variety of surfaces.
- ✓ Versatile - May be used for either manual cleaning, pressure washing, or through foam-generating equipment for foam cleaning. Excellent for floor cleaning.
- ✓ Hard Water Tolerant - Performance and risibility are not affected by moderate water hardness. Rinses freely to prevent spotting.
- ✓ Chlorine Compatible - Chlorine may be added at time of use for enhanced cleaning.
- ✓ Biodegradable - All detergents used to manufacture this product are biodegradable.

PHYSICAL PROPERTIES

Appearance	:	Clear, green thin water-based liquid
Odor	:	Slight
pH (as is)	:	13.0-13.5
Density	:	8.99 lb/gallon
Foam Level	:	High
Shelf Life	:	1 year from date of manufacture
Composition	:	Alkaline builders, solvents, nonionic and anionic surfactants

DIRECTIONS FOR USE

When used on soft metals such as aluminum and galvanized, monitor concentrations and contact time to avoid potential damage.

The directions below are general recommendations only. It is acceptable to use this product at higher

TECHNICAL DATA SHEET

800 Development Ave. ■ Chambersburg, PA 17201 ■ 1-800-345-1329 ■ www.afcocare.com



or lower concentrations depending on soil load and other conditions. Rinse thoroughly with potable water after use.

Consult your AFCO/Zep technical representative for specific use applications.

General Purpose Cleaning:

Use 2 to 6 fluid ounces of AFCO 5756 per gallon of water (16 to 47 mL/L) and apply by spraying or wiping. Hand scrub if necessary. Follow with potable water rinse.

Foam Cleaning:

Use 2 to 6 fluid ounces of AFCO 5756 per gallon of water (16 to 47 mL/L) and foam the resultant solution onto soiled surfaces. Hand scrub if necessary. Follow with potable water rinse.

Pressure Washing:

Use 2 to 6 fluid ounces of AFCO 5756 per gallon of water (16 to 47 mL/L) and apply the resultant solution to soiled surfaces. Hand scrub if necessary. Follow with potable water rinse.

SAFETY

Effective on stainless steel, floors, walls, hoods, ovens, grills, machinery, glass and many other hard surfaces. When used on soft metals such as aluminum and galvanized steel, monitor concentrations and contact time to avoid potential damage.

DANGER

Corrosive! Contact with undiluted product causes severe skin burns and serious eye damage. Consult the product's Safety Data Sheet (SDS) for complete safety information.