



Tornado Liquid Drain Cleaner (AFCO 7233)

GENERAL DESCRIPTION

Tornado Liquid Drain Cleaner (AFCO 7233) is a specially formulated spore-based concentrate designed to be used in drains and grease traps in food processing plants, restaurants, and commercial buildings. When used on a regular basis, AFCO 7233 reduces the accumulation of grease in sumps, drains, and traps.

AFCO 7233 contains microorganisms combined with natural biological enhancers, micronutrients, and macro-nutrients that are capable of degrading a wide range of oils and greases under aerobic and anaerobic conditions.

MAJOR BENEFITS

Regular use of AFCO 7233 will:

- ✓ Reduce odors,
- ✓ Reduce grease build-ups,
- ✓ Prevent blockages,
- ✓ Lower grease disposal costs,
- ✓ Save on line jetting.

PHYSICAL PROPERTIES

Appearance	:	Hazy colorless liquid
Odor	:	None
Density	:	8.33 lbs. per gallon
pH	:	6.0 - 8.0
Shelf Life	:	6 Months

TECHNICAL DATA SHEET

550 Development Ave. • Chambersburg, PA 17201 • 1-800-345-1329 • www.afcocare.com



DIRECTIONS FOR USE

Mix well before use.

Drain Lines and Down Pipes:

Use AFCO 7233 a minimum of 2 times weekly to a maximum of 4 times depending on the usage of the building. Add product in amounts listed below by pouring directly into the drain pipe starting on the lowest floor and working up at a rate of one floor each day.

<u>Pipe Size</u>	<u>Dosage</u>	<u>Frequency</u>
2 Inch	4 ounces	2 times/week
4 inch	8 ounces	2 times/week
6 inch	12 ounces	2 times/week
8 Inch	16 ounces	2 times/week

Grease Traps:

For less than 150 gallon trap (20 cubic feet capacity), add 10 ounces of product daily by pouring in a sink or pipeline closest to the trap. This should be done at night or when the traps are used the least. After adding, flush down with a cup of lukewarm water. For grease traps from 150 to 750 gallons (21 to 99 cubic feet), add 15 ounces daily using the same procedure. For grease traps from 750 to 1500+ gallons (100 to 200+ cubic feet), purge with 1.5 gallons and then use a maintenance dose of 20 ounces per day.

Septic Tanks:

Add 1 pint per 25 cubic feet capacity for the initial treatment. Thereafter, use 8 ounces per week. This may be poured directly into a toilet and flushed. If septic tank has become clogged and odorous, add 1 gallon of product directly to the tank through the manhole.

Portable Toilets:

Add one gallon directly and cover the solids with water to aid digestion. Every time the toilet is pumped, start treatment over again with one gallon of product.

SAFETY

Consult the product's Safety Data Sheet (SDS) for complete safety information.