



Guard Trolley Oil FLC-30 (AFCO 8091)

GENERAL DESCRIPTION

Guard Trolley Oil FLC-30 (AFCO 8091) is designed for use in meat packing plants as a trolley lubricant. AFCO 8091 offers superior rust protection and minimal dripping. It can be used in all departments of poultry, fish, meat and general food processing plants.

PHYSICAL PROPERTIES

Appearance	:	Colorless to pale amber, oily liquid
Odor	:	Slight
Specific Gravity	:	0.845 - 0.883
Melting Point	:	-7°C/20°F
Viscosity	:	15 centistokes at 40°C/104°F

DIRECTIONS FOR USE

Float 2 to 4 inches of AFCO 8091 on top of the trolley lubricating tank. For best results heat to between 140 and 180°F (60 & 82°C). Actual usage may vary depending on operation and conditions. Use only as directed.

STORAGE

Store in original sealed container at 40 to 120°F (4.4 TO 49°C).
Protect from freezing.
When stored in original, unopened container, this product has unlimited shelf-life.

SAFETY

If contact with eyes occurs, rinse eyes for 15 minutes with clean, luke-warm flowing water. If irritation persists, see a physician. Consult the product's Safety Data Sheet (SDS) for complete safety information.

TECHNICAL DATA SHEET

550 Development Ave. • Chambersburg, PA 17201 • 1-800-345-1329 • www.afcocare.com



NOTE

AFCO 8091 is acceptable for use in federally inspected meat, poultry and food processing plants.