



Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 01/30/2026

Version: 1.2

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Foamight

Product Code: AFCO 8509

Intended Use of the Product

Use of the Substance/Mixture: Foaming alkaline cleaner/degreaser for use on food processing equipment in dairies, bakeries, and in meat and poultry processing plants. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO

800 Development Avenue

Chambersburg, PA 17201

T: 800-345-1329

www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Corr. 1C H314

Eye Dam. 1 H318

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe vapors, mist, spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P321 - Specific treatment (see section 4).
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Hazards

Other Hazards Not Contributing to the Classification: N/A.

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances: Not available, product is a mixture.

Mixture:

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	80-90	Not classified
2-Butoxyethanol	(CAS No.) 111-76-2	1-5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation: vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Sodium metasilicate	(CAS No) 6834-92-0	1-5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Pentasodium triphosphate	(CAS No.)7758-29-4	1-5	Not classified
Potassium hydroxide	(CAS No) 1310-58-3	1-5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
Isopropyl alcohol	(CAS No.) 67-63-0	1-5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts	(CAS No) 68081-81-2	1-5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Sodium xylene sulfonate	(CAS No.) 1300-72-7	0.1-1	Eye Irrit 2A, H319
Sodium hydroxide	(CAS No.) 1310-73-2	0.1-1	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Sodium diisopropylnaphthalenesulfonate	(CAS No) 1322-93-6	0.1-1	Eye Irrit. 2A, H319
Ethyl alcohol	(CAS No.) 64-17-5	0.1-1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
Sodium laureth (n=>3)sulfate	(CAS No.) 9004-82-1	0.1-1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401
Cocamide DEA	(CAS No.) 68603-42-9	0.1-1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412

Exact percentage composition of substances and/or ingredients may be withheld as a trade secret, in accordance with [29 CFR § 1910.1200 App E].

Full text of H-phrases: see section 16.

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes. Get immediate medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Seek medical attention immediately. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. Corrosive to eyes, respiratory system and skin.

Inhalation: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Skin Contact: Causes severe skin burns and eye damage.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: Not available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to soft metals.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sulfur oxides. Corrosive vapors. Sodium oxides. Phosphorus oxides.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow product to spread into the environment. Do NOT breathe (vapors, mist, spray). Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes. Corrosive vapors are released.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high or low temperatures, incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s)

Foaming alkaline cleaner/degreaser for use on food processing equipment in dairies, bakeries, and in meat and poultry processing plants For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

2-Butoxyethanol (111-76-2)		
Mexico	OEL TWA (mg/m ³)	120 mg/m ³
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m ³)	360 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	24 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Ontario	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m ³)	97 mg/m ³
Québec	VEMP (ppm)	20 ppm

Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³

Isopropyl alcohol (67-63-0)		
Mexico	OEL TWA (mg/m ³)	980 mg/m ³
Mexico	OEL TWA (ppm)	400 ppm
Mexico	OEL STEL (mg/m ³)	1225 mg/m ³

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mexico	OEL STEL (ppm)	500 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	1230 mg/m ³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m ³)	985 mg/m ³
Québec	VEMP (ppm)	400 ppm

Potassium hydroxide (1310-58-3)

USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³

Ethyl alcohol (64-17-5)

Mexico	OEL TWA (mg/m ³)	1900 mg/m ³
Mexico	OEL TWA (ppm)	1000 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
Ontario	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1880 mg/m ³
Québec	VEMP (ppm)	1000 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Alarm detectors should be used when toxic gases may be released.

Personal Protective Equipment: Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection. Gloves. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Other Information: When using, do not eat, drink or smoke.

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, fluorescent green
Odor	: Characteristic
Odor Threshold	: Not available
pH	: >12
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 105°C (221°F)
Flash Point	: None
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not flammable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Specific Gravity	: 1.07
Solubility	: Complete.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to soft metals.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Strong acids, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Thermal decomposition generates: Corrosive vapors. Sodium oxides. Sulfur oxides. Oxides of phosphorus.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. **pH:** >12

Serious Eye Damage/Irritation: Causes serious eye damage. **pH:** >12

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: Causes severe skin burns and eye damage.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)	
LD50 Oral Rat	>90000 mg/kg
Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	333 mg/kg
ATE (oral)	333.000 mg/kg body weight
Sodium metasilicate (6834-92-0)	
LD50 Oral Rat	600 mg/kg
Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat (mg/l)	124.7 mg/l/4h
Sodium diisopropyl naphthalenesulfonate (1322-93-6)	
LD50 Oral Rat	1350 mg/kg
2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rat	1680 mg/kg
LC50 Inhalation Rat (ppm)	450 ppm/4h
ATE (dermal)	0.680 mg/kg body weight
ATE (gases)	450.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
IARC Group	3
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.
Isopropyl alcohol (67-63-0)	
LD50 Oral Rat	4396 mg/kg
LD50 Dermal Rabbit	12800 mg/kg
LC50 Inhalation Rat	16000 ppm (Exposure time: 8 h)
IARC Group	3
Cocamide DEA (68603-42-9)	
LD 50 Dermal Rabbit	>2g/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified.

Sodium metasilicate (6834-92-0)	
LC50 Fish 1	210 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC50 Fish 2	210 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
2-Butoxyethanol (111-76-2)	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
Sodium hydroxide (1310-73-2)	
LC50 Fish 1	40 mg/l

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodemus subspicatus)
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)
Ethyl alcohol (64-17-5)	
LC50 Fish 1	9.468 (9.468 - 12.624) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) converted from ml/l
EC50 Daphnia 1	9268 (9268 - 14221) mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Cocamide DEA (68603-42-9)	
EC50 Algae	<10 mg/l (Exposure time: 72 h)
LC50 Crustacea	<10 mg/l (Exposure time: 48 h)
LC50 Fish	<10 mg/l (Exposure time: 96 h)

Persistence and Degradability: Not available.

Bioaccumulative Potential

Foamight (AFCO 8509)	
Bioaccumulative Potential	Not established.
Potassium hydroxide (1310-58-3)	
Log Pow	0.65
2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (at 25°C)
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25°C)
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Bioaccumulative Potential	Not established.

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide)
Hazard Class : 8
Identification Number : UN3266
Label Codes : 8
Packing Group : III
ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide)
Hazard Class : 8
Identification Number : UN3266
Packing Group : III
Label Codes : 8



Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-B

14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide)

Packing Group : III

Identification Number : UN3266

Hazard Class : 8

Label Codes : 8

ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide)

Packing Group : III

Hazard Class : 8

Identification Number : UN3266

Label Codes : 8



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Foamight (AFCO 8509)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Potassium hydroxide (1310-58-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
2-Butoxyethanol (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium metasilicate (6834-92-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium diisopropylnaphthalenesulfonate (1322-93-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts (68081-81-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium laureth (n=>3) sulfate (9004-82-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cocamide DEA (68603-42-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

Sodium hydroxide (1310-73-2)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Potassium hydroxide (1310-58-3)

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Sodium metasilicate (6834-92-0)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

2-Butoxyethanol (111-76-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - Skin Designations
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts (68081-81-2)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Isopropyl alcohol (67-63-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Ethyl alcohol (64-17-5)

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List

Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New York - Occupational Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium diisopropyl naphthalenesulfonate (1322-93-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts (68081-81-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium laureth (n=>3) sulfate (9004-82-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Cocamide DEA (68603-42-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by those regulations.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 01/30/2026

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B


Foamight (AFCO 8509)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

- NFPA Health Hazard** : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
- NFPA Fire Hazard** : 0 - Materials that will not burn.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

- Health** : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is given.
- Flammability** : 0 - Minimal Hazard.
- Physical** : 0 - Minimal Hazard.

Party Responsible for the Preparation of This Document

AFCO
800 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)